



Hold Down Cross Reference Chart

Minimum HB Rod Requirement

#	Hold Down	Capacity	Edge of Slab	Interior
1	(1)CS16	1,650	3/8	3/8
2	(2)CS16	3,300	1/2	1/2
3	HD2A	2,775	1/2	1/2
4	HD5A	3,705	1/2	1/2
5	HD6A	5,510	5/8 or 1/2 & 3/8	5/8 or 1/2 & 3/8
6	HD8A	7,685	3/4 or (2) 1/2	3/4
7	HD10A	9,900	3/4	3/4
8	HD14A	13,380	3/4 + 1/2	3/4 + 1/2
9	HD15	15,305	3/4 + 5/8	3/4 + 5/8
10	HDQ8/SD53	8,325	3/4	3/4
11	HTT16	3,480	1/2	1/2
12	HTT22	5,250	5/8 or 1/2 & 3/8	5/8 or 1/2 & 3/8
13	LTT19	1,205	3/8	3/8
14	LTT20B	1,750	3/8	3/8
15	MST60	4,990	5/8	5/8
16	(2)MST60	9,980	3/4	3/4
17	MST72	5,800	5/8	5/8
18	(2)MST72	11,600	(2) 5/8 or 3/4 + 3/8	(2) 5/8 or 3/4 + 3/8
19	MTT28B	4,455	3/8 + 3/8	3/8 + 3/8
20	PHD2	3,610	1/2	1/2
21	PHD5	4,685	3/8 + 3/8	3/8 + 3/8
22	PHD6	5,860	5/8 or 1/2 & 3/8	5/8 or 1/2 & 3/8
23	PHD8	6,730	5/8 or (2) 1/2	5/8 or (2) 1/2
24	STHD8	3,095/2,370	1/2	1/2
25	STHD10	3,725/3,230	1/2	1/2

	Edge of Slab Epoxy Limiting	Edge of Slab with Reducer	Interior of Slab Rod Limiting
3/8	NA		2,405
1/2	NA		3,905
5/8	5,372	7,050	7,050
3/4	7,360	10,000	10,000
7/8	10,907		